



THE WORLD LEADER IN FUME EXTRACTION TECHNOLOGY

AD Oracle iQ

LASER

Last Updated on 13.07.2018



The premier choice and best in class solution with unique features in a compact unit.

The 'Best in Class' high performance AD Oracle has now been further enhanced with the introduction of BOFA's new iQ Operating System, combining a range of unique features into one compact unit.

The iQ Operating System performs at two distinct levels. Operators benefit from ease of operation and clarity of real time information, the system also provides a cache of analytical data, enabling users to download performance and operating parameters for evaluation purposes.

The iQ system takes performance and safety parameters to a new level and ensures that maintenance downtime and ownership costs are kept to a minimum.

Technology



Intelligent (iQ) Operating System



DeepPleat DUO pre filter



HEPA filter



Automatic flow control (AFC) technology



Reverse flow air (RFA) technology



Advanced carbon filter (ACF) technology



Multi voltage sensing (MVS) unit



Patented technology



ProTECT service plan



SureCHECK quality standard

Key features of the AD Oracle iQ

Reverse Flow filter technology Standard

Auto sensing voltage (90v - 257v) - For global use Standard

Automatic Flow Control Standard

Advanced Carbon Filter technology Standard

Contact BOFA at <https://bofainternational.com/en/contact/>
<https://bofainternational.com/en/portal/datasheets/ad-oracle-iq/>



HEPA and Gas combined filter
Standard

Real time airflow reading
Standard

Filter status warnings
Standard

Remote diagnostics via USB
Standard

Interfacing
Optional

Optional Filter medias
Optional

High contrast display
Standard

Independent filter condition monitoring
Standard

'Run safe' operation
Standard

VOC gas sensor (Volatile Organic Compound)
Optional

On-board compressor
Optional

Technical specification

1. iQ display

2. On/off switch

3. Power cable

4. Signal / interface cable

5. Door hinge

6. Hose inlet connection -
75mm



7. Exhaust outlet

8. Motor cooling inlet

9. Door latch



Airflow through filters



Part numbers

Model	Part No.	24V Stop / Start	Filter change / System failure signal	VOC monitoring	Hose kit
AD Oracle iQ stainless steel	L1974	A2001	A2002	A2003	A1020008 75-50mm
AD Oracle iQ powder coated	L1964	A2001	A2002	A2003	A1020008 75-50mm

Replacement filters

Model	DeepPleat DUO pre filter	Combined filter
AD Oracle iQ	A1030156	A1030155

Technical data

	EU	US
Dimensions (HxWxD)	955 x 430 x 475 mm	37.60 x 16.93 x 18.70"
Cabinet construction	Brushed stainless steel / Powder coated mild steel	Brushed stainless steel / Powder coated mild steel
Airflow / Pressure	380m ³ /hr / 96mbar	223cfm / 96mbar
Electrical data	90v - 257v 1ph 50/60Hz Full load current: 12.5 amps / 1.1kw	90v - 257v 1ph 50/60Hz Full load current: 12.5 amps / 1.1kw
Noise level	< 60dBA (at typical operating speed)	< 60dBA (at typical operating speed)
Weight	65kg	143lbs
Approvals	CE	cUL

DeepPleat DUO pre filter specifications

Surface media area	12m ² approx
--------------------	-------------------------

DeepPleat DUO pre filter specifications

Filter media	Glass Fibre
Filter media construction	Maxi pleat with webbing spacer
Filter housing	Zintec mild steel
Filter efficiency	95% @ 0.9 microns
Inlet size	75mm
Dropout chamber size	16.2 litres
Filter media pleat size	200mm

Combined filter specifications

HEPA filter media	Glass fibre
HEPA media construction	Maxi pleat construction with webbing spacers
Filter efficiency	99.997% @ 0.3 microns
Treated activated carbon	15kgs
Filter housing	Zintec mild steel

Other languages

AD Oracle iQ
[German](#)

AD Oracle iQ
[Chinese](#)

Datasheet correct at time of publishing. For specific applications, please contact us for details.

